

# Easy & Secure LATCH System



Instruction Booklet

## **Table of Contents**

Message to Parents.2WARNINGS.3What are Special Anchor Points?.4
Rear-Facing Position Birth to 1 Year
Installing Your Car Seat in a Vehicle Using the Easy & Secure LATCH System 6
Forward-Facing Position 1 Year and Up
Installing Your Car Seat in a Vehicle Using the Easy & Secure LATCH System 14
Refer to the Owner's Manual Included with this Car Seat

### Message to Parents

You've purchased the Safe Embrace® II Convertible Car Seat with Easy & Secure LATCH (Lower Anchors and Tethers for Children) System. The Easy & Secure LATCH System makes it possible for you to install this car seat in your vehicle simply by connecting hooks on the car seat to special anchor points within your vehicle.

The Owner's Manual included with this car seat was developed for use with our basic Safe Embrace® Convertible Car Seat which does **not** include instructions for use of the Easy & Secure LATCH System. This Instruction Booklet tells you how to properly install the car seat with the Easy & Secure LATCH System. Please read and understand this Instruction Booklet to install this car seat. Refer also to the Owner's Manual for important information about use of the Safe Embrace Convertible Car Seat.

**DO NOT** allow others to use this car seat until they understand these instructions and the instructions in the car seat Owner's Manual. **Your child's safety depends on you!** 



### **WARNING**

Proper installation and use depends on you! If you do not follow the instructions in this Instruction Booklet or the Owner's Manual, your child could be at risk of striking the vehicle's interior during a sudden stop or crash, resulting in serious injury or death.




NEVER attach the car seat's
Easy & Secure LATCH System
hooks to anything but your vehicle's
specially designed anchor points.
Your vehicle must be equipped with
special anchor points compatible
with LATCH or ISOFIX to use the
Easy & Secure LATCH System.



**NEVER** alter your vehicle to create anchor points for the Easy & Secure LATCH System.

### What are **Special Anchor Points?**



Special anchor points are a pair of inverted "U" shaped metal bars attached directly to your vehicle's frame. These special anchor points are located where the vehicle seat bottom and seat back meet. Please refer to your vehicle owner's manual to determine if your vehicle is equipped with special anchor points.

When referring to your vehicle owner's manual for information on special anchor points, look for the "LATCH" or "ISOFIX" anchor points section.



**Forward-Facing Position** 1 Year and Up Pages 14 to 21






Once you have selected an acceptable seating location for the car seat (see car seat Owner's Manual), locate the special anchor points in your vehicle.



### **WARNING**

NEVER install the car seat in the rear-facing position in a vehicle seating location equipped with an airbag. The airbag impact can cause severe head injury or death. If your vehicle is equipped with a front passenger side airbag, please refer to your vehicle owner's manual for child restraint installation instructions.



Loosen the Easy &
Secure LATCH System straps. Press the release button on the Easy & Secure

release button on the Easy & Secure LATCH System buckle and pull the strap attached to the car seat tube.

Repeat this procedure to loosen the other strap.

Page 8

## Installing Your Car Seat in a Vehicle Using the Easy & Secure LATCH System



- Place the car seat on the vehicle seat facing the **rear** of the vehicle.
- Slide the Easy & Secure LATCH System strap to the end of the burgundy tube. Fasten the Easy & Secure LATCH System hook to the vehicle special anchor point.

Repeat this procedure to fasten the Easy & Secure LATCH System strap on the other side of the car seat to the corresponding vehicle special anchor point.



with both Easy & Secure LATCH System straps fastened to the vehicle special anchor points, push down on the car seat bottom and pull the free ends of the straps (one at a time) until all the slack is removed from the straps. The car seat should be snug against the vehicle seat. Make sure both straps are tightened evenly so the car seat does not lean.





After tightening both Easy & Secure LATCH System straps, make sure the base of the car seat is **flat** on the vehicle seat. If the car seat is sloped toward the vehicle seat back, your child will be too upright, allowing your child's head to droop forward.



If the base of the car seat is not flat on the vehicle seat, insert a rolled bath towel between the vehicle seat and the foot of the car seat. This will raise the foot of the car seat so that the base is flat on the vehicle seat.



FP14280 Easy & Secure Manual



Test your installation by pushing on the top of the car seat. The car seat should **NOT** easily rotate down.

Regularly check to ensure your car seat installation is secure.

#### **IMPORTANT!**

Please refer to the Owner's Manual included with the car seat. Read and follow the section, "Restraining Your Child" on pages 31-35.



on the car seat bottom,


press the release button on the Easy & Secure LATCH System buckle to loosen the strap.

With the strap loose, unfasten the Easy & Secure LATCH System hook from the vehicle special anchor point.

Repeat this procedure to loosen and unfasten the other strap.



Once you have selected an acceptable seating location for the car seat (see car seat Owner's Manual), locate the special anchor points in your vehicle.



Loosen the Easy & Secure LATCH System straps. Press the release button on the Easy & Secure LATCH System buckle and pull the strap attached to the car seat tube.

> Repeat this procedure to loosen the other strap.



- Place the car seat on the vehicle seat facing the **front** of the vehicle.
- Slide the Easy & Secure LATCH System strap to the bend in the burgundy tube. Fasten the Easy & Secure LATCH System hook to the vehicle special anchor point.

Repeat this procedure to fasten the Easy & Secure LATCH System strap on the other side of the car seat to the corresponding vehicle special anchor point.



With both Easy & Secure LATCH System straps fastened to the vehicle special anchor points, push down on the car seat with your knee and pull the free ends of the straps (one a a time) until all the slack is removed from the straps. The car seat should be snug against the vehicle seat. Make sure both straps are tightened evenly so the car seat does not lean.





Attach the tether strap hook to the tether anchor.

**Note:** For information on tether anchor locations in your vehicle, refer to your vehicle owner's manual. If you need to install a tether anchor, please refer to page 38 in your car seat Owner's Manual.

- Pull the free end of the tether strap to tighten.
- Fold or roll the excess tether strap and tuck it between the car seat and vehicle seat.



To remove the tether strap from the tether anchor:

Lift the tab on the adjuster to loosen the tether strap. Remove the tether strap hook from the tether anchor.





Test your installation of the car seat by rocking the car seat forward and backward. You should **NOT** be able to pull the back of the car seat away from the vehicle seat more than one inch.

Regularly check to ensure your car seat installation is secure.

#### **IMPORTANT!**

Please refer to the Owner's Manual included with the car seat. Read and follow the section, "Restraining Your Child" on pages 58-64.



While pushing down on the car seat armrest, press the release button on the Easy & Secure

LATCH System buckle to loosen the strap.

With the strap loose, unfasten the Easy & Secure LATCH System hook from the vehicle special anchor point.

Repeat this procedure to loosen and unfasten the other strap.

### Refer to the Owner's Manual Included with this Car Seat

Please refer to the Owner's Manual included with this car seat for other important information about: warnings; general information; selecting a vehicle seating location; setup; restraining your child; aircraft use; registration information; and cleaning and washing instructions.

#### **Consumer Information**

If you have any questions about installation or proper use of your car seat, please call Fisher-Price® Consumer Affairs toll-free at **1-800-432-KIDS**, between 8 AM and 5 PM EST, Monday through Friday. Hearing-impaired consumers using TTY/TDD equipment, please call 1-800-382-7470. Or write to:

Fisher-Price® Consumer Affairs 636 Girard Avenue East Aurora, New York 14052

## **✓** Safe Check

#### Rear-Facing (Birth-1 Year)

### **✓** SHOULDER STRAPS

...inserted in lower or middle blue slots

#### ✓ ADJUST

- ...seat position adjuster to recline
- ...car seat rear-facing

#### **✓** FASTEN

- ...Easy & Secure LATCH System straps to special vehicle anchor points
- ...5-point harness and adjust it to fit child snugly

#### **✓** EVALUATE

- ...to be sure car seat is **not** installed in a vehicle seating location equipped with an airbag
- ...installation to be sure car seat is in appropriate seating location and is a firm fit in vehicle
- ...to be sure 5-point harness is snug against child

#### Forward-Facing (1 Year and Older)

#### **√**SHOULDER STRAPS

...inserted in upper burgundy slots

#### **√**ADJUST

- ...seat position adjuster to upright
- ...car seat forward-facing

#### /Fasten

- ...Easy & Secure LATCH System straps to special vehicle anchor points
- ...tether strap to tether anchor
- ...5-point harness and adjust it to fit child snugly

#### **✓** EVALUATE

- ...installation to be sure car seat is in appropriate seating location and is a tight fit in vehicle
- ...to be sure 5-point harness is snug against child

## Fisher Price

#### 1-800-432-KIDS

Fisher-Price, Inc., East Aurora, New York 14052, U.S.A. ©1999 Mattel, Inc. All Rights Reserved. 

® and ™ designate U.S. trademarks of Mattel Inc.

Printed in U.S.A. 79704pr-0921